Model DRZ Quick, Clean, Quiet.

Looking for a cleaner way to clean clogged drains? The DRZ is the answer. Light and powerful for a machine of its size, the DRZ is ideal for clearing clogged sinks, tubs, and laundry drains in 1-1/4" to 3" drain lines up to 50 ft. long.

The variable speed power cable feed on the DRZ-PH gives you complete control as it feeds and retrieves the cable at up to 16 ft. per minute. The four foot guide tube means you never have to touch the cable so your hands, and the jobsite, stay clean.

Operate the machine horizontally on the kitchen counter or vertically on the floor next to the tub. The silent motor won't disturb your customers while on the job. Use the pneumatic pedal to keep your hands free to control the feed and guide hose.

The rust resistant aluminum drum carries up to 50' of 1/4" or 5/16", or 35' of 3/8" Flexicore wire rope center cable. A quick-change cartridge system allows you to switch to a different diameter cable without pulling the old cable out of the drum.

Weighing as little as 30 lbs. the lighweight machine is easy to handle. Use the carrying handle on top to carry to and from the job.









Model DRZ™

Flexicore¹

Heavy gauge wire is coiled around 49 strand wire rope and then heat treated. This cable has unequalled strength and the right amount of flexibility. It's so tough, it has a one year warranty against defect or breakage.

Flexicore Patent Nos. 2,244,735 and 2,849,870

Economy Drain Cleaner

The less expensive DRZ uses a patented Quick-Grip™ chuck instead of the variable speed power cable feed, and the cable is housed in a tough impact resistant plastic drum.



Cutter Set - Catalog #HECS

Cutter		Part Number	Application
	Arrow Head Starting Drill	АН	Starting Drill Gets water flowing
	Boring Gimlet	BG	For removing loose objects
	Down Head Boring Gimlet	DHBG	For removing loose objects Goes down waste, not up stack
	Flexible Spring Arrow Head Cutter	FAH	Starting Drill For sharp turns in small lines
8	1-1/4 Side Cutter Blade (2 piece set)	1-1/4 SCB	For cutting and scraping

	DRZ-PH with Power Cable Feed - Complete and Ready to Operate		
	Basic Unit Includes: Aluminum Drum, Variable Speed Power Cable Feed, Four Foot Guide Hose, 1/5 hp Motor w/Reverse Switch, Water-Proof Air Foot Switch, Quick Change Plastic Cartridge.		
PH-DRZ-A	with 50 ft. x 5/16" (50HE1-A-DH) cable.		
PH-DRZ-B	with 50 ft. x 5/16" (50HE1-AC) cable, and HECS cutter set.		
PH-DRZ-C	with 35 ft. x 3/8" (35HE2) cable, and HECS cutter set.		
PH-DRZ-D	with 50 ft. x 1/4" (50HE1-DH) cable.		

^{*}Orange listing denotes best selling model.

DRZ-PH with Power Cable Feed Specifications

Weight:	t: 30 lbs. (13.6 kg) (without cable)	
Dimensions:	: 20" deep (w/o Guide Hose) x 11" wide x 15" high (51 cm x 28 cm x 38 cm)	
Drum:	Heavy gauge stamped aluminum with inner drum to prevent cable tangling.	
Capacity:	50 ft. of 1/4" or 5/16" cable; 35 ft. of 3/8" cable. (All cables are left hand wound and reinforced with a wire rope center.)	
Power Cable Feed:	Variable Speed; Drives 1/4", 5/16" and 3/8" cables.	
Cutter Set:	Arrow Head, Boring Gimlet, Down Head Boring Gimlet, 1-1/4" Side Cutter Blade, Flexible Arrow Head Cutter.	
Motor:	1/5 hp, with forward-off-reverse switch, fuse protected.	
Foot Pedal:	Pneumatic foot pedal leaves operator's hands free to control cable.	